

# Strike First Corporation of America

## ABC Fire Extinguishers

### Detail & Submittal Sheet

#### ABC Extinguisher Features:

- Non corrosive pull pin
- Completely rechargeable
- Full hand grip for ease of operation
- Waterproof stainless steel gauge
- Aluminum valve
- Quick release hose
- Steel cylinder complete with cylinder skirt
- Steel 2 1/2" cylinder (1A-10BC)
- Cylinder has high corrosion and impact resistant finish (red epoxy)
- Vehicle bracket optional
- Most parts are interchangeable
- Individually packaged
- Labeled "Meets DOT Requirements"

Project: \_\_\_\_\_

Specification Reference: \_\_\_\_\_

Model Number: \_\_\_\_\_ Quantity: \_\_\_\_\_

Architect: \_\_\_\_\_

Contractor: \_\_\_\_\_

Distributor: \_\_\_\_\_

Approved By: \_\_\_\_\_

Date: \_\_\_\_\_

#### Standard Bracket Included



#### Optional Brackets At Extra Cost



**NOTE:** Standard brackets are included with all extinguishers at no additional cost. If specified, optional brackets are available at additional cost. All of the above brackets are designed to accommodate Strike First Corporation of America extinguishers. While most comparable sized extinguishers usually will function with the above brackets, we cannot assume responsibility for variations in cylinder dimensions among various extinguisher suppliers.

**Class A:** Paper, Wood, Cloth, Rubber, etc...

**Class B:** Flammable Liquids such as Gasoline, Oil, Paints, Solvents, etc...

**Class C:** Live electrical equipment



✓	Model/Description	Nominal Capacity	Shipping Weight	Cylinder Diameter	Overall Height	Overall Width	PSI	Range	U/L Rating	Coast Guard Approved
			Lbs.	In.	In.	In.		Feet		
<b>ABC Extinguishers</b>										
	ABC 2.5-W	2.5 lb	5	3 1/8	15 1/4	3 3/4	150	8-12	1A-10BC	-
	ABC 2.5-V	2.5 lb	5	3 1/8	15 1/4	3 3/4	150	8-12	1A-10BC	Yes
	ABC 5-ALV-W	5 lb	10 1/2	4 1/4	15 1/4	6 3/4	195	10-15	2A-10BC	-
	ABC 5-ALV-V	5 lb	10 1/2	4 1/4	15 1/4	6 3/4	195	10-15	2A-10BC	Yes
	ABC 5HP-ALV-W	5 lb	10 1/2	4 1/4	16 5/8	6 3/4	195	10-15	3A-40BC	-
	ABC 5HP-ALV-V	5 lb	10 1/2	4 1/4	16 5/8	6 3/4	195	10-15	3A-40BC	Yes
	ABC 10-W	10 lb	19 1/4	5 1/8	21 1/4	9 1/2	235	10-15	4A-80BC	Yes (w/-024)
	ABC 20-W	20 lb	35 1/4	7 1/8	24	9 1/2	235	12-18	10A-120BC	-
	ABC 30-W	30 lb	50 1/3	7 1/8	30 3/4	9 1/2	195	10-15	10A-120BC	-

V = Vehicle Bracket W = Wall Bracket HP = High Performance

SFCA 2010